

General description

- For star distribution system of 8 SAT IF and 1 terrestrial TV signal
- Exquisite tinplate and plastic case
- External power supply
- Control: 13/18V, 0/22KHz, DiSEqC2.0

Technical specifications

| T Y P E | | MS9012 | MS9016 | MS9024 |
|-----------------------------|-------------|----------------------------------|--------|--------|
| Number of outputs | | 12 | 16 | 24 |
| Frequency range | SAT IF | 950-2400MHz | | |
| | Terr.TV | 47-862MHz | | |
| Insertion loss | SAT IF | 4.0dB | 5.0dB | 6.0dB |
| | Terr.TV | 5.0dB | 6.0dB | 6.0dB |
| Rejection | Terr.TV/SAT | 25dB | 25dB | 25dB |
| | SAT/Terr.TV | 25dB | 25dB | 25dB |
| Return loss | Out-Out | 25dB | 25dB | 25dB |
| | SAT IF | 10dB | 10dB | 10dB |
| | Terr.TV | 12dB | 12dB | 12dB |
| Output | | 8dB | 8dB | 8dB |
| Output level for SAT IF | | 93dBuV | | |
| Output level for Terr.TV | | 100dBuV | | |
| Mains voltage | | 12-20V | | |
| Control signals | | 14/18V, 0/22KHz, DiSeqC 1.0, 2.0 | | |
| Power consumption | | 18V Power supply | | |
| Operation temperature range | | -20 - 50 | | |

