

- Digital-Ready Broadband
5-1000MHz Frequency Range
- High Quality Zinc Diecast Case
- EMI-RFI > -120dB

Model No.

- A102P 2 way splitter
- A103P 3 way splitter
- A103PB 3 way splitter balance
- A104P 4 way splitter
- A106P 6 way splitter
- A108P 8 way splitter



Technical specifications

TYPE		A102P	A103P	A103PB	A104P	A106P	A108P
Insertion loss (IN-OUT)	5-47 MHz	3.6 dB	3.5/7.5 dB	7 dB	7.1 dB	9.5 dB	10.5 dB
	47-470 MHz	3.6 dB	3.7/7.9 dB	7 dB	7.5 dB	9.5 dB	10.5 dB
	470-862 MHz	3.8 dB	3.9/8.1 dB	7 dB	8.0 dB	10.5 dB	11 dB
	862-1000 MHz	4.0 dB	4.0/8.1 dB	7 dB	8.0 dB	11 dB	12 dB
Isolation (OUT-OUT)	5-47 MHz	22 dB	22 dB	22 dB	22 dB	18 dB	18 dB
	47-470 MHz	22 dB	22 dB	22 dB	22 dB	18 dB	18 dB
	470-862 MHz	22 dB	22 dB	22 dB	22 dB	18 dB	18 dB
	862-1000 MHz	22 dB	22 dB	22 dB	22 dB	18 dB	18 dB
Return loss	5-47 MHz	20 dB	18 dB	18 dB	18 dB	18 dB	18 dB
	47-470 MHz	20 dB	20 dB	20 dB	20 dB	18 dB	18 dB
	470-862 MHz	20 dB	20 dB	20 dB	20 dB	18 dB	18 dB
	862-1000 MHz	20 dB	18 dB	18 dB	18 dB	18 dB	18 dB

TYPICAL TRACE

